

11) Publication number: 0 651 331 A1

②

EUROPEAN PATENT APPLICATION -

(21) Application number: 94307580.4

(51) Int. Ci.6: G06F 12/08

2 Date of filing: 17.10.94

30 Priority: 18.10.93 US 139598 18.10.93 US 138596 18.10.93 US 138790

18.10.93 US 138790 18.10.93 US 138652 18.10.93 US 138654 18.10.93 US 138651

(4) Date of publication of application: 03.05.95 Bulletin 95/18

(4) Designated Contracting States: CH DE ES FR GB IE IT LI NL

Applicant: CYRIX CORPORATION 2703 N. Central Expressway Richardson, Texas 75080 (US)

(2) Inventor: Bluhm, Mark 4545 Staten Island Plano, Texas 75082 (US) Inventor: Garibay, Raul A., Jr. 333 Meirose No.3B Richardson, Texas 75080 (US) Inventor: Quattromani, Marc A. 710 Willow Brook Ailen, Texas 75002 (US) inventor: Hervin, Mark W. 17601 Preston Road, No.156, Dallas Texas 75252 (US) Inventor: Patwa, Nital 5000 Old Shepard Place. No.1517, Plano Texas 75093 (US)

(A) Representative: Harris, lan Richard c/o D. Young & Co.,
21 New Fetter Lane
London EC4A 1DA (GB)

(4) A write buffer for a superpipelined, superscalar microprocessor.

A superscalar, superpipelined microprocessor having a write buffer located between the central processing unit core and memory cache. The write buffer stores the results of write operations to memory until the cache memory becomes available, i.e., when no high--priority reads are to be performed. The write buffer includes multiple entries that are split into two circular buffer sections for facilitating the interaction with the two core pipelines. Cross-dependency tables are provided for each write buffer entry to ensure that the data is written from the write buffer to memory in program order, while considering any prior data in the opposite section. Non-cacheable reads from memory are also ordered in program order with the writing of data from the write buffer. Features for performing misaligned writes, handling speculative execution, detecting and handling data dependencies and exceptions, and p rforming gathered writes are also induded within the microprocessor.

